

FORMATO REGGIA IN ACCIAIO - Lucida e Zincata



Formato	Resistenza	Carico di rottura	All.	Peso rotolo	Avvolgimento	Finitura	Rotoli x pallet	Diametro int/est	Resa
in mm	kg / mm ²	kg	%	kg				mm	m/kg
13 x 0,45	65	380	2	16	monospira	lucida	36	300 / 540	21,78
13 x 0,50	65	423	2	16	monospira	lucida	36	300 / 540	19,60
13 x 0,60	65	507	2	16	monospira	lucida / zincata	36	300 / 540	16,33
16 x 0,45	65	468	2	19	monospira	lucida	30	300 / 540	17,69
16 x 0,50	65	520	2	19	monospira	lucida	30	300 / 540	15,92
16 x 0,60	65	624	2	19	monospira	lucida / zincata	30	300 / 540	13,27
19 x 0,50	65	618	2	23	monospira	lucida	25	300 / 540	13,41
19 x 0,60	65	741	2	23	monospira	lucida / zincata	25	300 / 540	11,27
19 x 0,70	65	845	2	23	monospira	lucida	25	300 / 540	9,58
19 x 0,80	65	988	2	23	monospira	lucida / zincata	25	300 / 540	8,38
25 x 0,80	65	1300	2	30	monospira	lucida / zincata	18	300 / 540	6,37
25 x 0,90	65	1463	2	30	monospira	lucida	18	300 / 540	5,67
25 x 1,00	65	1625	2	30	monospira	lucida	18	300 / 540	5,10
32 x 0,80	65	1664	2	38	monospira	lucida / zincata	15	300 / 540	4,98
32 x 0,90	65	1872	2	38	monospira	lucida	15	300 / 540	4,92
32 x 1,00	65	2080	2	38	monospira	lucida	15	300 / 540	3,98